

**Clips – Bags of 100**  
LF x .75

**Screws – Boxes of 400**  
Decking Face Screw: LF x 1.5  
Porch Flooring: LF x .75

**Screws - Boxes of 400 Clear Stainless,  
500 Black Stainless**  
Cladding: LF x .75

### ◉ Benchmark Ash

SIZE	LF		CONVERSION	TOTAL SF	LBS/SF
1x4 Porch Flooring		÷	3.43 =		2.74
1x4		÷	3.25 =		2.60
1x6 Standard		÷	2.31 =		2.59
1x6 Max		÷	2.03 =		2.74
5/4 x 4		÷	3.43 =		3.09
5/4 x 5		÷	2.67 =		3.60
5/4 x 6		÷	2.35 =		3.10
5/4 x 6 Max		÷	2.1 =		3.57

SIZE	SF		CONVERSION	TOTAL LF	LBS/LF
1x4 Porch Flooring		x	3.43 =		0.8
1x4		x	3.25 =		0.8
1x6 Standard		x	2.31 =		1.12
1x6 Max		x	2.03 =		1.35
5/4 x 4		x	3.43 =		0.9
5/4 x 5		x	2.67 =		1.35
5/4 x 6		x	2.35 =		1.32
5/4 x 6 Max		x	2.1 =		1.7

### ◉ Benchmark Pine/ Kodiak

SIZE	LF		CONVERSION	TOTAL SF	LBS/SF
5/4 x 5 Porch Flooring		x	2.67 =		2.14
5/4 x 6		x	2.18 =		2.55
5/4 x 8		x	1.64 =		2.54

SIZE	SF		CONVERSION	TOTAL LF	LBS/LF
5/4 x 5 Porch Flooring		x	2.67 =		0.8
5/4 x 6		x	2.18 =		1.17
5/4 x 8		x	1.64 =		1.55

**○ Benchmark Ash**

SIZE	LF		CONVERSION		TOTAL SF	LBS/SF
1x4 T&G		÷	3.43	=		2.74
1x6 C20		÷	2.14	=		2.89
1x6 C23J		÷	2.14	=		2.89
1x6 T&G		÷	2.03	=		2.74
1x8		÷	1.6	=		2.74

SIZE	SF		CONVERSION		TOTAL LF	LBS/LF
1x4 T&G		X	3.43	=		0.8
1x6 C20		X	2.14	=		1.35
1x6 C23J		X	2.14	=		1.35
1x6 T&G		X	2.03	=		1.35
1x8		X	1.6	=		1.71

**○ Benchmark Pine**

SIZE	LF		CONVERSION		TOTAL SF	LBS/SF
1x6 C19		÷	2.31	=		1.80
1x6 C4		÷	2.18	=		1.74

SIZE	SF		CONVERSION		TOTAL LF	LBS/LF
1x6 C19		X	2.31	=		0.78
1x6 C4		X	2.18	=		0.8

**○ Spruce**

SIZE	LF		CONVERSION		TOTAL SF	LBS/SF
1x6 Ignite		÷	2.3	=		1.84
1x8		÷	1.74	=		1.91
1x9		÷	1.52	=		1.90

SIZE	SF		CONVERSION		TOTAL LF	LBS/LF
1x6 Ignite		X	2.3	=		0.8
1x8		X	1.74	=		1.1
1x9		X	1.52	=		1.25

→ [thermoryusa.com](http://thermoryusa.com)

Last updated: November 2021.  
All previous versions are null and void.